



# **PULSE**

AN OUT-OF-THE-BOX IP COMMUNICATION PLATFORM



Vingtor-Stentofon products are developed by the Zenitel Group and comprise a range of high quality communications equipment and systems. In business since 1901, Zenitel's products are recognized worldwide for offering high quality communications for both offshore and onshore installations. Primary system offerings in the Vingtor-Stentofon product portfolio are Public Address and Intercom. Zenitel and the company's global partner network also integrate these systems with other security devices such as Radio, CCTV, Access Control and Alarm for a comprehensive security solution.



PULSE STATIONS	4
PULSE STATION KITS	9
PULSE ACCESSORIES	10
PULSE LICENSES	13
PULSE GATEWAYS	14

# **PULSE INTERCOM STATIONS**

# 1008001000 / 1008001100

# IP DESK/WALL MASTER STATION WITH DISPLAY & HANDSET

- Connects directly to the IP network, no geographical limitations
- 85 dB audio pressure 1 meter from speaker
- Large high contrast display with backlight for excellent readability
- 10 freely programmable single-touch keys (DAK)
- Superb audio technology
  Integrated Web server for easy configuration and monitoring
- Remote software upgrade, configuration and monitoring
- Background Noise Cancellation 1008001000: White Color
- 1008001100: Black Color

# 1008000000

# IP DESK/WALL MASTER STATION WITH DISPLAY

- Connects directly to the IP network, no geographical limitations
- 85 dB audio pressure 1 meter from speaker
- Large high contrast display with backlight for excellent readability
  10 freely programmable single-touch keys (DAK)
  Superb audio technology
  Integrated Web server for easy configuration and

- monitoring
  Remote software upgrade, configuration and
- monitoring
- Background Noise Cancellation



# Size (WxHxD): 225 x 75 x 176mm Wt: 0.7kg

Accessories: 1008091100 Wall bracket for Desktop



# Size (WxHxD): 168 x 75 x 176mm Wt: 0.5kg

Accessories: 1008091100 Wall bracket for Desktop

# 1008007000

# IP DUAL DISPLAY STATION

- IP station with full access to all features in the AlphaCom exchange
- Remote software upgrade, configuration and monitoring
  Powered from the IP network cable using Power
- over Ethernet (PoE)
- Superb audio quality high bandwidth codec, active noise cancellation, acoustic echo cancellation and high output power amplifier
- Displays with backlight
- Background Noise Cancellation

# 1008015000

# IP OR MASTER WITH DISPLAY

- Connects directly to the IP network, no geographical limitations
- Large high contrast display with backlight for excellent readability
  Flat chemical resistant and anti-bacterial front
- surface for easy cleaning
  4 freely programmable single-touch keys (DAK)
- Superb audio technology possible to talk and listen at a distance (5m)
- Integrated web server for easy configuration and
- monitoring Background Noise Cancellation

# 1008031000

# **CRM-V IP FLUSH MASTER WITH** DISPLAY

- Connects directly to the IP network, no geographical limitations
- Large high contrast display with backlight for excellent readability
- White light behind all keys
- Four freely programmable single-touch keys (DAK)
- Superb audio technology Optional handset unit
- Remote upgrade, configuration and monitoring
- Background Noise Cancellation



# Size (WxHxD): 72 x 140 x 270mm Wt: 0.4kg

Accessories: 1007007010 Microphone for Dual Display Station



# Size (WxHxD): 125 x 280 x 30mm Wt: 0.63kg

Accessories: 1008098700 Flush Mount Back Box



# Size (WxHxD): 125 x 280 x 30mm Wt: 0.63kg

Accessories: 1008097500 Gooseneck Microphone, 1008097100 Handset, 1008098700 Flush Mount Back Box, 2810020004/5/6 Desk Stand

# 1008041100 / 1008042100

# **IP VANDAL RESISTANT SUBSTATION**

- · Connects directly to the IP network, no geographical limitation
- Dual Ethernet ports for connection of other IP device
- Possible connection to external IP video camera
- One relay output for door lock control or flash strobe light, etc.
- Remote software upgrade, configuration and monitoring
- Stainless steel front (A304)
- Background Noise Cancellation 1008041100: 1 Button
- 1008042100: 2 Buttons



# Size (WxHxD): 92 x 180 x 46mm Wt: 0.8kg

Accessories: 1008098100 Flush Mount Back Box, 1008098000 On Wall Back Box

# 1008072220 / 1008072120

# IP HEAVY DUTY TELEPHONE, **HOTLINE**

- Made for critical communication in rough environments like roads, tunnels, ships
- Extremely water and dust resistant (IP67)
- Highly durable with 5mm aluminum casing and stainless steel components
- Magnetic reed hook-switch ensures minimal wear and tear
- Supports VoIP with SIP and CCoIP with AlphaCom
- Supports local power and Power over Ethernet (PoE) Integrated data switch with advanced networking and security functions
- Supports HD Voice
- 1008072220:w/ Door, 1008072120:without Door

# 1008041150

# **IP VANDAL RESISTANT** SUBSTATION CONFORMAL COATED

- Connects directly to the IP network, no geographical limitation
- Dual Ethernet ports for connection of other IP device
- Possible connection to external IP video camera
- One relay output for door lock control or flash strobe light, etc.
- Remote software upgrade, configuration and monitoring
- Background Noise Cancellation
- Stainless steel front (A304)



# Size (WxHxD): 92 x 180 x 46mm Wt: 0.8kg

Accessories: 1008098100 Flush Mount Back Box, 1008098000 On Wall

# 1008072200 / 1008072100

# IP HEAVY DUTY TELEPHONE, FULL **KEYPAD**

- Made for critical communication in rough environments like roads, tunnels, ships
- Extremely water and dust resistant (IP67)
- Very durable with 5mm aluminum casing and stainless steel components
- Magnetic reed hook-switch ensures minimal wear
- Supports VoIP with SIP and CCoIP with AlphaCom
- Supports local power and Power over Ethernet (PoE)
- Integrated data switch with advanced networking and security functions
- Supports HD Voice
- 1008072200:w/ Door, 1008072100:without Door

# Size (WxHxD): 205 x 320 x 148mm Wt: 5.4kg

Accessories: 1020600992 IRR-3 Relay Box 24V DC or 220V AC - Signal Unit WT - IP-66

# Size (WxHxD): 205 x 320 x 148mm Wt: 5.4kg

Accessories: 1020600992 IRR-3 Relay Box 24V DC or 220V AC - Signal Unit WT - IP-66

# 1008051000

# **IP VANDAL RESISTANT SUBSTATION, 3 GANG BACK BOX**

- Connects directly to the IP network, no geographical limitation
- Dual Ethernet ports for connection of other IP device
- Possible connection to external IP video camera
- One relay output for door lock control or flash strobe light, etc.
- Remote software upgrade, configuration and monitoring Background Noise Cancellation
- Stainless steel front (A304)



# Size (WxHxD): 114 x 160 x 63mm Wt: 0.8kg

Accessories: 1008098300 3 Gang Flush Mount Back Box

# THE **TURBINE SERIES**



The Turbine Series provides innovative features and a cutting edge design that will change the way we look at intercom.

All IP stations in the Vingtor-Stentofon Turbine Series utilize the latest technology and Vingtor-Stentofon's 65+ years of experience in the audio communications industry to create stunning audio quality.

# 1008111030

# TCIS-3

- Amazing sound pressure level when needed
- Background noise cancellation
- Dirt, dust and water resistant Class IP 66 Built to last with robust die-cast aluminum frame
- Class IK 08
- Designed according to the norm for hearing
- Support wide set of IP and networking standards
- Black thermoplastic front plate with one button Ideal for Building Security and Public
- Environments

# 1008111010

# TCIS-1

- Amazing sound pressure level when needed
- Background noise cancellation
- Dirt, dust and water resistant Class IP 66
- Built to last with robust die-cast aluminum frame - Class IK 08
- Designed according to the norm for hearing impaired
- Support wide set of IP and networking standards
- Yellow thermoplastic front plate with one button + M and C
- Ideal for Industrial Applications

# 1008111020

# TCIS-2

- Amazing sound pressure level when needed
- Background noise cancellation
- Dirt, dust and water resistant Class IP 66
- Built to last with robust die-cast aluminum frame - Class IK 10
- Designed according to the norm for hearing impaired
- Support wide set of IP and networking standards
- Stainless steel front plate with one button
- Ideal for Building Security and Public Environments



# Size (WxHxD): 120 x 180 x 70mm Wt: 0.8kg

Accessories: 1008140010 TA-1 Turbine Compact On Wall Box, 1008140020 TA-2 Turbine Compact Flush Back Box, 1008140050 TA-5 Wall Bracket for Turbine Compact

# 1008111040

# TCIS-4

- Amazing sound pressure level when needed
- Background noise cancellation
- Dirt, dust and water resistant Class IP 66
- Built to last with robust die-cast aluminum frame Class IK 08
- Designed according to the norm for hearing impaired
- Support wide set of IP and networking standards
- Black thermoplastic front plate with one labelled
- Unique labeling solution with PMOLED display Ideal for Building Security and Public
- Environments



# Size (WxHxD): 120 x 180 x 70mm Wt: 0.8kg

Accessories: 1008140010 TA-1 Turbine Compact On Wall Box. 1008140020 TA-2 Turbine Compact Flush Back Box, 1008140050 TA-5 Wall Bracket for Turbine Compact

# 1008111050

# TCIS-5

- Amazing sound pressure level when needed
- Background noise cancellation
- Dirt, dust and water resistant Class IP 66
- Built to last with robust die-cast aluminum frame - Class IK 08
- Designed according to the norm for hearing
- Support wide set of IP and networking standards
- Black thermoplastic front plate with two labelled huttons
- Unique labeling solution with PMOLED display
- Ideal for Building Security and Public Environments



# Size (WxHxD): 120 x 180 x 70mm Wt: 0.8kg

Accessories: 1008140010 TA-1 Turbine Compact On Wall Box, 1008140020 TA-2 Turbine Compact Flush Back Box, 1008140050 TA-5 Wall Bracket for Turbine Compact



# Size (WxHxD): 120 x 180 x 70mm Wt: 0.8kg

Accessories: 1008140010 TA-1 Turbine Compact On Wall Box, 1008140020 TA-2 Turbine Compact Flush Back Box, 1008140050 TA-5 Wall Bracket for Turbine Compact



# Size (WxHxD): 120 x 180 x 70mm Wt: 0.8kg

Accessories: 1008140010 TA-1 Turbine Compact On Wall Box, 1008140020 TA-2 Turbine Compact Flush Back Box, 1008140050 TA-5 Wall Bracket for Turbine Compact

# TCIS-6

- Amazing sound pressure level when needed
- Background noise cancellation
- Dirt, dust and water resistant Class IP 66
- Built to last with robust die-cast aluminum frame - Class IK 08
- Designed according to the norm for hearing impaired
- Support wide set of IP and networking standards
- Black thermoplastic front plate with scrolling unit for calling to an unlimited number of places
- PMOLED display
- Ideal for Building Security and Public Environments



# Size (WxHxD): 120 x 180 x 70mm Wt: 0.8kg

Accessories: 1008140010 TA-1 Turbine Compact On Wall Box, 1008140020 TA-2 Turbine Compact Flush Back Box, 1008140050 TA-5 Wall Bracket for Turbine Compact

# 1008115060

# TCIV-6

- HD Video at up to 25 FPS (720p)
- Wide angle lens (90°)
- MJPEG and H.264 for integration with most Video solutions
- Designed according to Disability Act requirements Background noise cancellation
- Dirt, dust and water resistant rating IP-65
- Built to last with robust die-cast aluminum frame Supports wide set of IP and networking standards
- Black thermoplastic front plate with scrolling unit for calling to an unlimited number of places
- PMOLED display
- Ideal for Building Security and Public Environments



# Size (WxHxD): 120 x 180 x 70mm Wt: 0.8kg

Accessories: 1008140010 TA-1 Turbine Compact On Wall Box, 1008140020 TA-2 Turbine Compact Flush Back Box, 1008140050 TA-5 Wall Bracket for Turbine Compact

# 1008115020

# TCIV-2

- HD Video at up to 25 FPS (720p)
- Wide angle lens (90°)
- MJPEG and H.264 for integration with most Video solutions
- Designed according to Disability Act requirements
- Background noise cancellation
- Dirt, dust and water resistant rating IP-65
- Built to last with robust die-cast aluminum frame Supports wide set of IP and networking standards
- Stainless steel front plate with one button
- Ideal for Building Security and Public **Environments**

# 1008115030

# TCIV-3

- HD Video at up to 25 FPS (720p)
- Wide angle lens (90°)
- MJPEG and H.264 for integration with most Video solutions
- Designed according to Disability Act requirements
- Background noise cancellation
- Dirt, dust and water resistant rating IP-65
- Built to last with robust die-cast aluminum frame
- Supports wide set of IP and networking standards Black thermoplastic front plate with one button
- Ideal for Building Security and Public **Environments**



# Size (WxHxD): 120 x 180 x 70mm Wt: 0.8kg

Accessories: 1008140010 TA-1 Turbine Compact On Wall Box, 1008140020 TA-2 Turbine Compact Flush Back Box, 1008140050 TA-5 Wall Bracket for Turbine Compact

# 1008116010

# TMIS-1 TURBINE MINI

- Background noise cancellation
- Built to last with robust die-cast aluminum frame
- White thermoplastic front plate with one button



# Size (WxHxD): 116 x 116 x 40 mm Wt: 0.3 kg

Accessories: 1008140020 TA-2 Turbine Compact Flush Back Box, 1008140030 TA-3 Turbine Compact Flush Back Box, 1008140120 TA-12 Turbine Mini On-Wall Backbox Black, 1008140130 TA-13 Turbine Mini On-Wall Backbox White

# 1008116020

# TMIS-2 TURBINE MINI

- **Background Noise Cancellation**
- Vandal Resistant Design 11 Gauge Stainless Steel Faceplate



# Size (WxHxD): 114 x 114 x 55 mm Wt: 0.5 kg

Accessories: 1008140020 TA-2 Turbine Compact Flush Back Box, 1008140030 TA-3 Turbine Compact Flush Back Box, 1008140120 TA-12 Turbine Mini On-Wall Backbox Black, 1008140130 TA-13 Turbine Mini On-Wall Backbox White



# Size (WxHxD): 120 x 180 x 70mm Wt: 0.8kg

Accessories: 1008140010 TA-1 Turbine Compact On Wall Box, 1008140020 TA-2 Turbine Compact Flush Back Box, 1008140050 TA-5 Wall Bracket for Turbine Compact

# 1008140110

# **TURBINE DEMO SUITCASE**

- 1 pc Netgear ProSafe 8P 10/100 PoE Ethernet Switch 1 pc D-Link DIR-600 150 Wireless 11n Router
- 1 pc Planet PoE Splitter
- 1 pc CAT5 Flat Cable 1.5m
- 1 pc CAT5 Flat Cable 30cm
- 1 pc CAT5 Flat Cable 10cm



Size (WxHxD): 285 x 240 x 150 mm Wt; 3.7 kg

# TFIE-1

- CCoIP/VoIP intercom for industrial environments
- Dual Ethernet connectivity for redundant networks
- PoE powered

- Auxiliary DC power for redundancy DIP functionality for use with AlphaCom servers SIP/VoIP functionality for use with 3rd-party systems
- Dual relay outputs
- 6 configurable I/Os
- Dust- and water-protected to IP-66 Accessories include Handheld PTT, Headset with ON/OFF and PTT and Handset with PTT
- Monitoring and self-diagnostics of critical
- Visible status indicators on front panel
- **Background Noise Cancellation**



# Size (WxHxD): 178 x 345 x 101 mm Weight: 1.9 kg

Accessories: 1023533311 EMMAI-1H Mic, 1023533312 EMMAI-2H Mic, 1008140230 TA-23 Handset, AK5850HS Headset, 1008140225 TA-22B Cable & Plugbox, 1008140100 TA-10 Relay Module

# 1008123020

# TFIX-2

- Ex IP intercom for potentially explosive atmospheres Directive 94/9/EC
- Ethernet compatible 2-wire interface
- DIP functionality for use with AlphaCom servers
- SIP/VoIP functionality for use with 3rd-party systems
- Dust- and water-protected to IP66
- Monitoring and self-diagnostics of critical functionality
- Visible status indicators on front panel
- Background Noise Cancellation

# 1008122020

# TFIE-2

- CCoIP/VoIP intercom for industrial environments
- Dual Ethernet connectivity for redundant networks
- PoE powered
- Auxiliary DC power for redundancy DIP functionality for use with AlphaCom servers SIP/VoIP functionality for use with 3rd-party
- systems
- Dual relay outputs
- 6 configurable I/Os
- Dust- and water-protected to IP-66 Accessories include Handheld PTT, Headset with ON/OFF and PTT and Handset with PTT
- Monitoring and self-diagnostics of critical functionality
- Visible status indicators on front panel
- **Background Noise Cancellation**



# Size (WxHxD): 178 x 345 x 101 mm Weight: 1.9 kg

Accessories: 1023533311 EMMAI-1H Mic, 1023533312 EMMAI-2H Mic, 1008140230 TA-23 Handset, AK5850HS Headset, 1008140225 TA-22B Cable & Plugbox, 1008140100 TA-10 Relay Module

# 1008123030

# TFIX-3

- Ex IP intercom for potentially explosive atmospheres Directive 94/9/EC Ethernet compatible 2-wire interface
- DIP functionality for use with AlphaCom servers
- SIP/VoIP functionality for use with 3rd-party systems
- Dust- and water-protected to IP66
- Monitoring and self-diagnostics of critical functionality
- Visible status indicators on front panel
- Background Noise Cancellation

# 1008123010

# TFIX-1

- Ex IP intercom for potentially explosive atmospheres Directive 94/9/EC
- Ethernet compatible 2-wire interface
- DIP functionality for use with AlphaCom servers
- SIP/VoIP functionality for use with 3rd-party systems
- Dust- and water-protected to IP66
- Monitoring and self-diagnostics of critical functionality
- Visible status indicators on front panel
- Background Noise Cancellation



# Size (WxHxD): 178 x 345 x 101 mm Weight: 4 kg

Accessories: 1023533511 EMMAX-1H Mic, 1008150030 TAX-3 Handset, AK5850HS Headset, 1008150025 TAX-2B Cable & Plugbox

# 1008123040

# TFIX-4

- Ex IP intercom for potentially explosive atmospheres - Directive 94/9/EC Ethernet compatible 2-wire interface
- DIP functionality for use with AlphaCom servers
- SIP/VoIP functionality for use with 3rd-party systems
- Dust- and water-protected to IP-66
- Monitoring and self-diagnostics of critical functionality
- Visible status indicators on front panel
- Background Noise Cancellation



# Size (WxHxD): 178 x 345 x 101 mm Weight: 4 kg

Accessories: 1023533511 EMMAX-1H Mic, 1008150030 TAX-3 Handset, AK5850HS Headset, 1008150025 TAX-2B Cable & Plugbox



# Size (WxHxD): 178 x 345 x 101 mm Weight: 4 kg

Accessories: 1023533511 EMMAX-1H Mic, 1008150030 TAX-3 Handset, AK5850HS Headset, 1008150025 TAX-2B Cable & Plugbox



# Size (WxHxD): 178 x 345 x 101 mm Weight: 4 kg

Accessories: 1023533511 EMMAX-1H Mic, 1008150030 TAX-3 Handset, AK5850HS Headset, 1008150025 TAX-2B Cable & Plugbox

# **PULSE STATION KITS**

# 1008093000

# **IP MASTER STATION KIT**

- Made for Critical Communication over IP
- Supports full keyboard including direct access keys (DAK) and dynamic keys
- Supports handset and headset

- Superb audio quality OdB (600 Ohm) output to Public Address Relay output for e.g. door lock control and tamper alarm input
- Dual Ethernet ports for connection of other IP
- Remote software upgrade, configuration and monitoring

# 1008090200

# **IP SUBSTATION KIT**

- Made for Critical Communication over IP
- Superb audio quality
  OdB (600 Ohm) output to Public Address
- Relay output for e.g. door lock control and tamper alarm input
- Dual Ethernet ports for connection of other IP devices
- Enables manufacturing of EN 81-28 and 81-70 compliant lift stations
- Remote software upgrade, configuration and monitoring



# Size (WxHxD): 88 x 152 x 20mm Wt: 0.13kg

Accessories: 1008099000 Display for IP Master Station Board, 5 Pieces



# Size (WxHxD): 72 x 110 x 20mm Wt: 0.1kg

Accessories: 1008091000 Mounting and Assembly Kit for IP Substation

# 1008090250

# **IP SUBSTATION KIT, CONFORMAL COATED**

- Made for Critical Communication over IP
- Superb audio quality
- OdB (600 Ohm) output to Public Address
- Relay output for e.g. door lock control and tamper alarm input
- Dual Ethernet ports for connection of other IP
- Enables manufacturing of EN 81-28 and 81-70 compliant lift stations
- Remote software upgrade, configuration and monitoring

# 1008131020

# TKIS-2 VOIP INTERCOM MODULE

- DIN-rail mountable, clips included
- Add VoIP/CCoIP to your parking solution, cash point, vending machine, et al Build your own IP Intercom station or help point
- Make your own 10W IP Speaker Control relay and I/Os over IP
- Supports AlphaCom, Pulse and SIP (for use with any IPBX)
- Supports a wide set of IP networking standards
- Remote software upgrade, configuration and monitoring
  Powered from the IP network cable using Power
- over Ethernet (PoE) Advanced audio technology like automatic
- gain and volume adjustment, background noise cancellation, open duplex, etc. 1008131010 TKIS-1 Turbine Kit (Compact Card)

# 1008132010

# TKIE-1 TURBINE EXTENDED KIT

- IP station kit with extended functionality
- Dual RJ45 for Ethernet connectivity (with switch)
  Dual relays (DPDT)
- 6 configurable I/Os (input, output or LED-driving) Line-in/Line-out connectivity for connection to
- audio devices
- Header for connecting audio accessories
- Option to connect high-power relay module TA-10 High quality Turbine™ class output with 10W
- amplifier
- · Full open duplex and digital noise reduction.



# Size (WxHxD): 72 x 110 x 20mm Wt: 0.1kg

Accessories: 1008091000 Mounting and Assembly Kit for IP Substation



# Size (WxHxD): 117 x 71 x 32 mm Wt: 0.1 kg

Accessories: 1008140170 TA-17 electret mic



# Size (WxHxD): 100 x 65 x 25 mm Wt: 0.1 kg

Accessories: 1008140100 TA-10 Relay Module



# **ON WALL BACK BOX**

On wall mount back box for IP Flush Master Stations



### Size (WxHxD): 125 x 280 x 34mm Wt: 0.5kg

Related items: 1008031000 IP FLUSH Master, Display



On wall Mount Back Box for Vandal Resistant

# Size (WxHxD): 92 x 180 x 52mm Wt: 0.8kg

Related items: 1008041100 IP Vandal Resistant Substation, 1007056100 Vandal Resistant Substation, 1007056200 Vandal Resistant ant Substation 2 Button

# 1008140030

# **TA-3 TURBINE COMPACT FLUSH MOUNT BACK BOX**

Flush mount back box for Turbine Mini Stations



# Size (WxHxD): 96 x 96 x 64mm Wt: 0.4kg

Related items: Turbine Mini Stations TMIS-1 & TMIS-2

# 1008140010

# **TA-1 TURBINE COMPACT ON WALL BOX**

For on-wall mounting of all Turbine Compact Stations



# Size (WxHxD): 120 x 180 x 62mm Wt: 0.8kg

Related items: All Turbine Compact Stations

# 1008098100

1008098000

ON WALL BACK BOX

Substation, IP and Traditional

# **FLUSH MOUNT BACK BOX**

Flush Mount Back Box for Vandal Resistant Substation IP and Traditional



# Size (WxHxD): 80 x 168 x 50mm Wt: 0.8kg

Related items: 1008041100 IP Vandal Resistant Substation, 1007056100 Vandal Resistant Substation

# 1008098800

# **FLUSH MOUNT BACK BOX**

Backbox for handset module for IP Flush Master



# Size (WxHxD): 58 x 270 x 40mm Wt: 0.3kg

Related items: 1008097100 Handset

# 1008098300

# **3 GANG FLUSH MOUNT BACK BOX**

• Flush Mount Back Box for IP Vandal Resistant Substation, 3 Gang Back Box



Related items: 1008051000 IP Vandal Resistant Substation - 3 Gang

# 1008098700

# **FLUSH MOUNT BACK BOX**

· Flush mount back box for IP Flush Master Stations inclusive IP OR Master Station



# Size (WxHxD): 98 x 145 x 66mm Wt: 0.8kg

# Size (WxHxD): 116 x 270 x 40mm Wt: 0.5kg

Related items: 1008015000 IP OR Master, 1008031000 IP Flush Master, Display

# 1008140020

# **TA-2 TURBINE COMPACT FLUSH BACK BOX**

Flush mount back box for Turbine Compact Stations



# Size (WxHxD): 96 x 96 x 90 Wt: 0.5kg

Related items: All Turbine Compact Stations

# 1008140120 / 1008140130

# TA-12 / TA-13 TURBINE MINI **ON-WALL BACK BOX**

TA-12 Black / TA-13 White



# Size (WxHxD): 124 x 122 x 65 mm Wt: 0.4kg

Related items: Turbine Mini Stations TMIS-1 & TMIS-2

# 1008140050

# **TA-5 WALL BRACKET FOR TURBINE COMPACT**

Wall bracket for Turbine Compact Stations



# Size (WxHxD): 169 x 109 x 10 mm Wt: 0.2 kg

Related items: All Turbine Compact Stations

# **EMMAI-1H HANDHELD INDUSTRIAL MIC, 1 BUTTON, IP66**

- Handheld microphone for Industrial application
- PTT-key on handset
- Noise-cancelling microphone
- HD-voice compatible Designed for Turbine industrial intercoms

# 1023533312

# **EMMAI-2H HANDHELD INDUSTRIAL** MICROPHONE, COMPACT

- Handheld microphone for Industrial stations
- Curled cord
- PTT key on handset
- Noise cancelling microphone
- HD voice compatible
- Designed for Turbine Industrial intercom stations

# 1008140230

# **TA-23 INDUSTRIAL HANDSET FOR TURBINE WITH PTT**

- Rugged handset for Industrial application
- PTT-key for simplex operation in extremely noisy environments
- Noise-cancelling microphone High quality digital background noise reduction
- HD-voice compatible
- IP Rating: IP66
- Designed for Turbine Industrial Intercom







# Size (WxHxD): 71 x 99 x 39 mm Weight: 0.8 kg

Additional Information: IP-66

# Size (WxHxD): 44 x 68 x 21.5 mm Weight: 0.22 kg

Additional Information: IP-66 Wall bracket included

# Size (WxHxD): 200 x 70 x 50 mm Weight: 310 g

# 1008150030

# **TAX-3 HANDSET FOR TURBINE EX** WITH PTT

- Rugged handset for Ex application PTT-key for simplex operation in extremely noisy environments
- Noise-cancelling microphone
- High quality digital background noise reduction
- HD-voice compatible
- IP Rating: IP-66
- Designed for Turbine Ex explosion-proof intercoms

# **AK5850HS**

# **AK5850HS EX-APPROVED HEADSET**

- Rugged headset for Ex application
- Noise-cancelling microphone High quality digital background noise reduction
- HD-voice compatible
- High quality audio
- Optional in-ear monitors may be connected for added damping in extreme environments
- IP Rating: IP-66
- Standard 4-pole Nexus connector for easy connection/replacement
- For use with 1008150025 Ex-approved Cable for headset with PTT
- Designed for Turbine Ex explosion-proof intercoms

# 1008140225 / 1008150025

# TA-22B / TAX-2B CABLE AND PLUGBOX FOR AK5850HS HEADSET

- 10m cable
- Compact, rugged plugbox with PTT for Industrial application IP Rating: IP66
- For use with AK5850HS Headset
- TA-22B for Turbine Industrial intercoms
- TAX-2B for Turbine Ex intercoms







# Size (WxHxD): 200 x 70 x 50 mm Weight: 310 g

Size (WxHxD): 210 x 150 x 70 mm Weight: 400 g

Accessories: TA-22B / TAX-2B Ex-approved Cable and Plugbox

Length: 10 m

# **EMMAR-1H HANDHELD MIC FOR ECPIR-3P**

- Stainless steel bracket included
- Push-To-Talk button
- 3-meter curly cord
- Equipped with locking DIN plug
- High quality digital background noise reduction

# 1023533511

# **EMMAX-1H HANDHELD EX MIC**

- Handheld microphone for Ex applications
- PTT key
- Noise cancelling microphone
- High quality digital background noise reduction
- IP66 Rating
  Designed for Turbine Ex explosion-proof intercom stations

# 1008140100

# **TA-10 RELAY MODULE**

- Designed for use with Turbine Industrial IP Intercom stations
- Dual high-power relays (DPDT) Up to 400VAC /48 VDC per relay
- Up to 6A current per relay
- Heavy-duty spring-loaded terminals with spare grounding terminals
- Powered by Turbine Industrial stations (TFIE-x) or Turbine Extended Kit (TKIE-1)







# Size (WxHxD): 71 x 99 x 39 mm Weight: 0.8 kg

Additional Information: IP-66

# 1023300010

# **ELSIR-10C NETWORK CEILING LOUDSPEAKER**

- Steel fire dome
- 10W Class D, built-in amplifier
- >100 dB SPL
- Ideal for Micro Zone PA and systems that require a limited number of speakers
- Each speaker is individually addressable and monitored
- Ideal for speakers installed in remote locations, e.g. roads and railways
- Remote software upgrade and configuration Relay output for remote control, e.g. doors, signal
- lamps, gates
- Powered from the IP network cable using Power over Ethernet (PoE)
- Ideal for Building Security, Infrastructure and Industrial projects

# Size (WxHxD): 44 x 68 x 21.5 mm Weight: 0.22 kg

Additional Information: IP-66 Wall bracket included

Related items: 1008122010 TFIE-1, 1008122020 TFIE-2, 1008132010 TKIE-1

Size (WxHxD): 100 x 50 x 40 mm Wt: 0.1 kg

# 1023301310

# **ELSII-10H NETWORK HORN LOUDSPEAKER**

- 10W Class D, built-in amplifier
- Dust and water tight IP 67
- >116 dB SPL
- Ideal for Micro Zone PA and systems that require a limited number of speakers
- Each speaker is individually addressable and monitored
- Ideal for speakers installed in remote locations, e.g. roads and railways
- Remote software upgrade and configuration Relay output for remote control, e.g. doors, signal lamps, gates
- Powered from the IP network cable using Power over Ethernet (PoE)
- Ideal for Building Security, Infrastructure and Industrial projects

# 1009800140

# **USBBTN VS-CLIENT USB BUTTON**

- USB Button for controlling VS-Client
- Accepts and terminates calls Switches between duplex mode and Push-To-Talk
- LED indicators for call states
- Polished steel base with non-slip sponge rubber



Size (Height x Dia.): 17 x 56 mm Cable Length: 1 m



Size (Diam x Depth): 199 x 111 mm Wt: 1.4 kg



Size (WxHxD): 186 x 144 x 207 mm Wt: 1.8 kg

# **PULSE LICENSES & EXTENSIONS**



# 1009660001

# **PULSE BASIC LICENSE**

# Includes Support for:

- 16x VS Intercom Extensions 16x VSVS-IMT

- Licensed Features:

  3rd-Party SIP-Client Extensions
  SIP Telephone Trunking

  - VS-Client Extensions

# 1009662001

# **PULSE-SERVER TELTRUNK**

- Connects Pulse to iPBX
- Allows communication to analog and ISDN telephone systems via gateways
- Number and name presentation Caller ID
- Easy to configure, monitor and manage
- Easy installation and networking connects systems over IP
- Use digits during conversation open door by

# 1009660002

# **PULSE ENTERPRISE LICENSE**

# Includes Support for:

- 16x VS Intercom Extensions
- VS-IMT
- VS-SDK

# Licensed Features:

- 3rd-Party SIP-Client Extensions
- SIP Telephone Trunking
- VS-Client Extensions
- Pulse Multisite Trunking
- Advanced Audio
- I/O Extensions

# 1009662101

# **PULSE-SERVER MULTISITE TRUNKING**

- Networking of Pulse sites
- Easy to configure and set up
- HD Audio support
- Supports supplementary functions such as call transfer, call forwarding, ringlist and service profiles
- One license is required to configure ONE Trunk Route between two sites

Required: Pulse Enterprise License

# 1009661101 / 1009661106

# **PULSE-SERVER VS-CLIENT EXTENSIONS, 1X & 6X**

- Turn your PC into a Vingtor-Stentofon Intercom Access a wide range of critical communication services including intercom, public address, radio and telephony from your PC
- Supports HD Voice and VS Intercom technology
- Supports call history, contacts and favorites
- Can be operated with mouse, USB button or PC keyboard

=

3

П

Designed to work with touch screens

106 - Peter Brink

4

2

5

8

0

3

6

9

#

# 1009665301 / 1009665306

# **PULSE-CLIENT IOEXT, 1X & 6X**

- Enables custom features and integration capabilities for VS-Intercoms
- Examples of integration: access control integration, video management integration, and special notification services
- Integration and custom features are made by activating a script on a VS-Intercom event
- Call states
- Custom scripts can be made using LUA scripts and
- control

Required: Pulse Enterprise License

- The following VS-Intercom events are supported:
- Registration status toward SIP and Pulse server - DTMF events
- Linux Shell commands Integration available: Lenel TruPortal access

# 1009661201 / 1009661206

# **PULSE-SERVER SIP-CLIENT EXTENSIONS, 1X & 6X**

- Extend Pulse with
- IP telephones IP DECT
- PC & mobile VoIP clients
- Easy to configure and set up
- Up to 10 SIP station licenses and accounts can be included in one Pulse installation

# 1009665101 / 1009665106

# **PULSE-CLIENT ADVANCED AUDIO,** 1X & 6X

- Enables the station to use the G729 Codec in Pulse mode
- G729 is low-bandwidth codec using 8 kbit/s
- Ideal codec for connections with limited bandwidth

Required: Pulse Enterprise License

# Size (WxHxD): Resizable

Accessories: 1009800140 USBBTN USB Button

# **PULSE GATEWAYS**



# 3006204094

# **AUDIOCODES MP-114 GATEWAY**

- Connects AlphaCom XE system to external telephone system such as PABXs and the public telephone network
- Supports 4 analog telephone lines
- Web management for easy configuration and installation



# Size (WxHxD): 220 x 42 x 172mm Wt: 0.5kg

Accessories: 2200002000 19" Rack Mounting Kit for Audio Codes, 1009642002/4/8/16 SIP Trunking License

# 2200003000

# **GSM GATEWAY**

- Connects AlphaCom XE to GSM for external calls World wide GSM coverage using quad band GSM (800/900/1800/1900)
- Web interface for configuration



# Size (WxHxD): 145 x 173 x 45mm Wt: 1.2kg

Accessories: 1009642001 SIP Trunking License

# 3006204099

# **AUDIOCODES MP-118 GATEWAY**

- Connects AlphaCom XE system to external telephone system such as PABXs and the public telephone network
- Supports 8 analog telephone lines
- Web management for easy configuration and installation



# Size (WxHxD): 220 x 42 x 172mm Wt: 0.5kg

Accessories: 2200002000 19" Rack Mounting Kit for Audio Codes, 1009642002/4/8/16 SIP Trunking License

# 2200002000

# 19" RACK MOUNTING KIT FOR **AUDIO CODES**

· Allows mounting in standard 19" rack



# Size: 1HU

Accessories: 3006204094 AudioCodes MP-114 Gateway, 3006204099 AudioCodes MP-118 Gateway



# www.zenitel.com

A100K11287 18.1.2016